

M50 P1 Wedge Barrier



G-2000 Series

- ASTM F2656-07 M50 P1 Certified
- Hydraulic or Electro-Mechanical
- Multiple Barrier Widths (8' - 14'6")
- Hot-Dip Galvanize or Color Coat to Specifications
- 12" Frame Foundation Depth (14" with Drainage)

Features

- Bi-Directional Flashing Lights
- EFO Deploy to Secure Position ≤ 1.5 Second (EM) 5 HP Motor ≤ 2 Second (EM) 3 HP Motor ≤ 1 Second (Hydraulic)
- 100% Submersible (EM)
- Design Allows for Less Stress on Barrier Parts from Vehicle Traffic

Benefits

- Low Maintenance: 250,000+ Cycles with NO Parts Replacement
- No Rebar Needed for Installation
- No Springs or Pneumatic Assists
- No Chains:
 - Allows the Barrier to be Installed on Sloped Areas



Additional Options

- Touchscreen Controls
- Basic Controls
- Wrong Way Vehicle Loop
- Suppression Vehicle Loop
- Over Speed Detection
- Heat Trace
- Sump Pump
- Installation Kit
- Battery Backup
- Remote EFO
- AC/Fan Unit

US Patent No. 9,771,696
US Patent No. 9,856,615
US Patent No. 10,094,082

M50 P1 Wedge Barrier



AISC
CERTIFIED
FABRICATOR



 **ASIS 16**
accolades
Security's Best **Winner**



HQ: 4303 Innovation Loop
Marble Falls, TX 78654
Offices: Middle East



www.gibraltarp.com



info@gibraltarp.com
(800) 495-8957